

Digital Flow Meter Gauges



Gauges and Digital Flow Meter to match your application

Additional models, sizes, makes, capacities and options are available.

Please contact us for information, consulting or engineering assistance.

Digital Flow Meter

	Digital Flow Meter	Digital Low Flow Meter
Flow range	3 – 30 GPM (10 – 100 l/min)	0.3 – 3 GPM (1 to 10 l/min)
Typical accuracy	+/- 5% (factory calibrated)	+/- 1.5% (field calibrated)
Maximum Pressure Drop	1.7 PSIG (0.12 bar) @ full flow	2 PSIG (0.14 bar) @ full flow
Port size	1" NPT	1" NPT
Power	2 x AAA batteries (included)	2 x AAA batteries (included)
Electronic features	resettable batch count non resettable cumulative count	Flow rate, resettable batch count non resettable cumulative count
Weight	2 lbs (0.9kg)	2 (0.9)

- Designed for outdoor use from 14 to + 130 deg F (-10 to +54 deg C) on fuel transfer applications diesel, gasoline, kerosene and jet fuel.
- For protection, install your digital flow meters inline after a strainer or filter.

Gauges



	CI-20	GV-10	VG-30	PG-30	PG-60
Type	Pressure Gauge	Vacuum Gauge	Vacuum Gauge	Pressure Gauge	Pressure Gauge
Range	0-60 PSI	0-30 "HG	0-30 "HG	0-30 PSI	0-60 PSI
Connection	Center Back 1/8" NPT	Center Back 1/8" NPT	Bottom 1/4" NPT	Bottom 1/4" NPT	Bottom 1/4" NPT
Design type	Dry, color coded	Dry, color coded	Liquid filled, SS	Liquid filled, SS	Liquid filled, SS
Dial Diameter	2"	2"	2 1/2"	2 1/2"	2 1/2"
Weight	3.5 oz	3.5 oz	6 oz	6 oz	6 oz

Critical Fuel Technology, Inc.

PO Box 395, Madison Lake, MN 56063 Phone 507-995-0070 Fax 507-243-3595 www.criticalfueltech.com